



## TX22 Cross

Shimano Deore XT 12-speed / Bosch Performance Line CX / 625Wh / Disc

Article	Inch	Frame size	Color
102220701	27,5"	Unisex, 50 cm	golden green matt
102220702	27,5"	Unisex, 55 cm	golden green matt
102220703	27,5"	Unisex, 60 cm	golden green matt

### Drive System

#### Motor

Bosch Performance Line CX, Gen. 4

36 Volt, Mid-engine

Output power 250 Watt

#### Display

Nyon, 3,2 inch touch-colour display with remote

#### Battery

Bosch Frame battery fully integrated

Energy content: 625 Wh

Voltage: 36 Volt

Capacity: 16,7 Ah

Technical changes and changes in equipment reserved, color deviations possible.

General	Component	Description
General	Frame	Aluminum 6061, Bosch-Interface, 100 mm suspension travel
	Head set	Acros AZX-212, tapered
	Fork	Suntour Mobie25 Air, 100 mm travel with lockout-function
	Shifting System	Shimano Deore XT RD-M8100, 12-speed, Shadow Plus
	Derailleur	---
	Brakes	Shimano Deore XT BR-M8100 (front 180 mm / rear 180 mm)
	Headlight	Supernova Mini 2 Pro, with High beam, 160 / 100 LUX
	Rear light	Busch & Müller, Shine Evo LED, integrated in the carrier
	Carrier	integrated in the frame, with Racktime System, with spring flap
	Saddle	Ergon SFC30
	Seat post	EXA KSP900i, remote dropper post
	Pedals	Marwi SP-102 Flat Pedal, aluminum
	Kickstand	Comp Flex, rear kickstand
	Chainguard	Herrmans chainguard
	Mudguard	Alumee, aluminum
Other	Abus Bordo folding lock keyed alike, permissible total weight 140 kg	
Weight	31,2 kg	
Cockpit	Stem	Humpert Ergotec Barracuda
	Handlebars	Humpert Ergotec Ergobar, 680 mm
	Grips	Ergon GP1, with clamp
	Shift lever	Shimano Deore XT SL-M8100, I-Spec EV, 12-speed
	Brake lever	Shimano Deore XT BL-M8100
Wheels/Tires/Drivetrain	Tires	Schwalbe Marathon Plus MTB, 57-584, reflex
	Rims	Schürmann YAK 25 Disc aluminum, 36 holes
	Spokes	Niro 2,0 mm, black
	Front Hub	Shimano Deore XT HB-M8110, 15 x 100 mm, Centerlock, 36 holes
	Rear Hub	Shimano Deore XT FH-M8110, 12 x 142 mm, Centerlock, 36 holes, Micro-Spline
	Sprocket	Shimano Deore CS-M6100, 12-speed, 10-51 teeth, Micro-Spline
	Chain	KMC E12 EPT
	Inner bearing	---
Bottom bracket	Miranda aluminum, 170 mm, KMC Chaining 38 teeth incl. chainguard	
Gear ratio (f:r)	38 teeth : 10-51 teeth	