



13ZEHN

Shimano Deore XT 11-speed / Bosch Performance Line CX / 625Wh / Disc

Article	Inch	Frame size	Color
102220751	27,5"	Gents, 50 cm	black matt
102220752	27,5"	Gents, 55 cm	black matt
102220753	27,5"	Gents, 60 cm	black matt
102220755	27,5"	Ladies, 47 cm	black matt
102220756	27,5"	Ladies, 50 cm	black matt
102220757	27,5"	Ladies, 55 cm	black matt
102220775	27,5"	Ladies, 47 cm	red matt
102220776	27,5"	Ladies, 50 cm	red matt
102220777	27,5"	Ladies, 55 cm	red matt

Drive System

Motor

Bosch Performance Line CX, Gen. 4

36 Volt, Mid-engine

Output power 250 Watt

Display

Nyon, 3,2 inch touch-colour display with remote

Battery

Bosch Frame battery fully integrated

Energy content: 625 Wh

Voltage: 36 Volt

Capacity: 16,7 Ah

Technical changes and changes in equipment reserved, color deviations possible.

General	Component	Specification
General	Frame	Aluminum 6061, Bosch-Interface
	Head set	Acros AZX-212, tapered
	Fork	Suntour Mobie25 Coil, 100 mm travel with lockout-function
	Shifting System	Shimano Deore XT RD-M8000, 11-speed, Shadow Plus
	Derailleur	---
	Brakes	Shimano Deore BR-MT410 (front 180 mm / rear 180 mm)
	Headlight	Supernova Mini 2 Pro, with High beam, 160 / 100 LUX
	Rear light	Busch & Müller, Shine Evo LED, integrated in the carrier
	Carrier	integrated in the frame, with Racktime System, with spring flap
	Saddle	Selle Royal Essenza
	Seat post	Humpert Ergotec Atar, patent, 31,6 mm, 300 mm
	Pedals	Marwi SP-823
	Kickstand	Comp Flex, rear kickstand
	Chainguard	SKS Chainbow_E
	Mudguard	Alumee, aluminum
	Other	Abus Bordo folding lock keyed alike, permissible total weight 140 kg
Weight	29,2 kg	
Cockpit	Stem	Humpert Ergotec Octopus 50, angle adjustable
	Handlebars	Humpert Ergotec Ergobar, 630 mm
	Grips	Ergon GP1, with clamp
	Shift lever	Shimano Deore SL-M5100, I-Spec EV, 11-speed
Brake lever	Shimano Deore BL-M4100	
Wheels/Tires/Drivetrain	Tires	Schwalbe Super Moto-X, 62-584, reflex
	Rims	Schürmann YAK 25 Disc aluminum, 36 holes
	Spokes	2,0 mm, black
	Front Hub	Shimano Alivio HB-MT400, 15 x 100 mm, Centerlock, 36 holes
	Rear Hub	Shimano Alivio FH-MT400, 12 x 142 mm, Centerlock, 36 holes
	Sprocket	Shimano SLX CS-M7000, 11-speed, 11-46 teeth
	Chain	KMC E11 EPT
	Inner bearing	---
Bottom bracket	Miranda aluminum, 170 mm, KMC Chaining 38 teeth	
Gear ratio (f:r)	38 teeth : 11-46 teeth	